



End Guardrail

2m Section

Walk Thru C-Stirrup with Hoist

750 lb Hoist:
 250 lb Maximum Distributed Load Capacity
 Maximum point load: 120 lb/linear ft.

1,000 lb Hoist:
 550 lb Maximum Distributed Load Capacity
 Maximum point load: 120 lb/linear ft.

1,500 lb Hoist:
 1,000 lb Maximum Distributed Load Capacity
 Maximum point load: 120 lb/linear ft.

1 man = 250 lb
 2 men = 500 lb

2	Released for project	BJA	09-29-15												
REV	Revision Description	By	Date												
DEBUR AND BREAK SHARP EDGES															
Material: Assembly		Weight: 478 LBS													
Treatment: N/A															
Raw material part number:		Dimensions in [] are in mm Tol. ISO 2768-m													
Assembly		<table border="1"> <tr> <td>></td> <td>0,5</td> <td>6</td> <td>30</td> <td>120</td> <td>400</td> </tr> <tr> <td><</td> <td>6</td> <td>30</td> <td>120</td> <td>400</td> <td></td> </tr> </table>		>	0,5	6	30	120	400	<	6	30	120	400	
>	0,5	6	30	120	400										
<	6	30	120	400											
Scale Size 1:24 B/A3		TOL. ±0.1 ±0.2 ±0.3 ±0.5 ±0.8 Machined surfaces 12.5 ISO 1302													
CAD generated drawing. Do not manually update. Do not scale drawing.		Unless otherwise stated tolerances in inches													
Approvals By:	Date:	Fractions	Decimals												
Drawn BJA	08-21-13		X ± .060 XX ± .015 XXX ± .005												
Approved:	XX-XX-XX		ALL ± .5°												
		Product Line/Project: Workage													
		REV. 2													
		Part No. L1003-270													
		Sheet 1 of 1													



The information contained in this drawing is the sole property of Bee Access Products. Any reproduction in part or whole without the written permission of Bee Access Products is strictly prohibited.

Walk Thru 2m Workage